

Hydraulic Drills



Hydraulic hammer drill HD13

- Flow min-max: 26-34 l/min
- Ideal flow: 20 l/min
- Max pressure: 150 bar
- Tolerable back pressure: max 10 bar
- Bit attachment type: SDS max
- Bit rotation speed: 400 rpm



HYDRAULIC POWERED MAGNETIC DRILL

- Cutter Capacity: 12-60 mm
- Stroke Length: 160 mm
- Speed: 50 - 400 rpm
- Flow Range: 10 - 40 lpm
- Pressure: 3250 Psi max
- Connection: HTMA Flat Face Connectors



AK 46 PISTOL CORE DRILL TOOL

- Flow 20 - 30 l/min
- Pressure 105 - 170 bar
- Bit attachment 1-1/4" standard
- mod S 30 to 100mm



AK 50 CORE DRILL FOR HEAVY DUTY

- Weight: 13 kg
- Dimension: 54 x 22 cm
- Bit attachment: 1 - 1.1/4" int 1/2" BSP
- Drilling capacity min/max 50 / 700 mm
- Speed (RPM) 90 - 760
- Flow: 30 - 38 l/min



Stanley DL07

- Chuck capacity 1/2" / 12mm
- Flow range 11,3 - 38 lpm
- Working pressure 70 - 140 bar
- Full relief setting 155 bar
- Weight 7,8 lbs / 3,5 kg



Stanley ID07

- Torque 675 Nm
- Input flow range 15 45 lpm
- Input pressure 50 - 140 bar
- Weight 3,3 kg

Technical Diving Equipment Pomtec BV

Conradweg 22
4612PD Bergen op Zoom
The Netherlands

T: +31 164 745500
F: +31 164 745599

E: sales@pomtec.com
I: www.pomtec.com



Stanley HD45

- Output 0 - 300 rpm
- Input flow range 26 - 34 lpm
- Input pressure 105 - 140 bar
- Optimum flow 30 lpm
- Weight 20,4 kg