



POMMEC - 1 DIVER MOBILE VIDEO SYSTEM

- Integrated monitor
- Single Video Channel
- Light control
- Solid DVR based system
- 500 GB SSD




POMMEC - 2 DIVER MOBILE VIDEO SYSTEM

- Integrated monitor
- Two video Channels
- Two light controls
- Solid DVR based system
- 500 GB SSD



POMMEC - RACK MOUNT VIDEO SYSTEM

- 1 to 4 video Channels
- 1 to 4 light controls
- Integrated SSD
- Solid DVR based system
- Several versions possible



POMMEC - VIDEO CAMERA

- SD or HD version
- Integrated LED ring or no integrated LED ring
- Complete with Kirby Morgan Bracket



POMMEC - LED LIGHT

- LED light
- Complete with Kirby Morgan Bracket



E-VISION

- 15" integrated foldable LCD monitor
- Single Video Channel
- Light control
- 500 GB hard disk drive
- Optional: emergency save battery



C-VISION SOLO

- 12.1" Screen
- Single Video Channel
- Light control
- 500 GB hard disk drive
- C-Tecnic's Dive Station Software



C-VISION

- 15.6" Screen
- Two Video Channels
- Light Control
- Integrated Comms (2 wire standard, 4 wire optional)
- C-Tecnic's Dive Station Software



C-VISION NANO

- Connection via USB interface
- Light control
- Supplied with C-Tecnic's Dive Station video recording software
- In-Built rechargeable battery



C-VISION R

- Rack mounted system
- Live recording of 2 video streams
- 2 wire 3 divers communication (4 wire optional)
- C-Tecnic's Dive Station Software



E-VISION R

- Rack mounted system
- 1, 2 or 3 channel versions
- 500 GB HDD per channel
- Light control



C-VISION NANO - RACK MOUNT

- Rack mounted system
- Connection via USB interface
- Light control
- Supplied with C-Tecnic's Dive Station video recording software



C-DVR Blackbox

- Record 2 video channels independently
- Internal battery backup
- 1 TB per channel
- Auto record/stop



CT3015 COLOUR CAMERA

- 1000 TV Lines
- 1000 mtr
- Diameter 30 mm
- Length 135mm ex connector
- Effective Pixels: 752 (H) x 582 (V) PAL



CT4006 LED LIGHT

- 1100 lumens @ 800 mA
- Cool White
- Viewing Angle 125°
- Length 80 mm
- Diameter 30 mm



DEPTH TRANSDUCER

- Depth range: 0-100msw
- Accuracy 0.025% of scale
- Weight ~200 gram
- Transducer element - 109 mm x 16 mm
- With cable whip - 780mm x 21.6mm (at mould)



HELMET BRACKETS

- Suitable for CT4006 + CT3015
- Pair (single is also possible)
- For diameter 30 mm